



## Lynx™ Hand-Held 2D Reader

### FEATURES

- Omni-directional scanning
- Support most popular 1D, 2D and Postal codes
- Autodiscrimination of linear and 2D codes
- Image capture
- Intuitive aiming
- Multi-standard interface

### APPLICATIONS

- Shop floor:
  - WIP
  - Tracking
  - Quality Control
- Document handling:
  - Front-Desk/Postal applications
  - Shipping & Receiving

### GENERAL DESCRIPTION

Datalogic, the leading European manufacturer of Hand-Held CCD and Laser readers, further improves its offer with the introduction of a state-of-the-art and powerful "bi-dimensional" reader: the **Lynx™**.

Based on a matricial CCD sensor (640 x 480 pixel), the **Lynx™** allows "omnidirectional" reading of the most common 1D symbologies as well as a wide variety of 2D and stacked codes. Furthermore, the **Lynx™** can be used for "image-based" applications like signature capture, OCR and so on. In fact, with the **Lynx™** the user captures the whole image of the object to be identified no matter how it is orientated, thus avoiding any alignment constraint between the reader and the symbol/image to be read/captured.

The captured image can be processed on board for 1D or 2D symbologies, or downloaded in different formats for image processing on the host side.

Aiming at the image to be captured is really easy and intuitive thanks to the "double-click" trigger for Point & Read, and to the "five dot pointer" that mark the four corners and center of the reading area.

The **Lynx™** is available in two models that are specifically addressed to standard (D302) and high resolution (D302 E) codes. Both models are equipped with a multi-standard interface to allow connection to the host via RS232 or wedge emulation interface.

The software tool "visual setup" included in the **Lynx™** package allows easy configuration of all the parameters for personalizing the reader to the application, as well as a quick view of the downloaded images.

The **Lynx™** is suitable for applications in even the most demanding environments thanks to its rugged case and "Industrial" electromagnetic protection. The **Lynx's™** Firmware can be in-field updated for easy maintenance and investment protection.



# MODELS AND ACCESSORIES

MODEL	DESCRIPTION	COILED CAB.	STRAIGHT CAB.	ORDER NO.
LYNX™ D302	2D Hand-Held reader			901601010
LYNX™ D302 E	2D Hand-Held reader for High Resolution codes			901601020
ACCESSORIES				
CAB362	RS232 cable, 9-pin female connector (DCE config.)	•		90A051330
CAB363*	RS232 cable, 25-pin female connector (DCE config.)	•		90A051340
CAB364*	RS232 cable, 25-pin male connector (DTE config.)	•		90A051350
CAB327	RS232 cable, 9-pin female connector (DCE config.)		•	90G001070
CAB328*	RS232 cable, 25-pin female connector cable (DCE config.)		•	90G001080
CAB320*	RS232 cable, 25-pin male connector (DTE config.)		•	90G001000
CAB390	USB type A external power supply		•	90A051730
CAB391	IBM/PS2 wedge minidin external power supply	•		90A051740
Operator's Manual	Software manual for Lynx™ series			included
PG110 (110 Vac)	Power supply unit 12 VDC			B9751057
PG220 (220 Vac)	Power supply unit 12 VDC			B9751027

\*Power supply available on pin 9 or 25 of the connector.

## SPECIFICATIONS

POWER SUPPLY	10 to 30 VDC	2D Codes	PDF417, MaxiCode, DataMatrix (ECC200), QR, AZTEC, MICRO PDF 417, MACRO PDF 417
CONSUMPTION	200 mA @ 12VDC (stand-by) 300 mA @ 12 VDC (typical) 440 mA @ 12 VDC (peak current)	Postal	Postnet, Planet, Australian, Japanese, KIX CODE, ROYAL MAIL
AIMING	Visible laser diode @ 650 nm	IMAGE AND SIGNATURE CAPTURE	640 x 480 VGA (8 bit gray scale) 320 x 240 CIF (8 bit gray scale)
MAX. RESOLUTION		INTERFACES	RS232, Wedge AT IBM; USB
D302	linear: 5 mils; datamatrix: 10 mils	DIMENSIONS	203 x 117.2 x 68.9 mm
D302 E	linear: 3 mils; datamatrix: 5 mils	WEIGHT	265 g (without cable)
ANGULAR FIELD OF VIEW	28.6° (H) x 21.9° (V): D302 model 21.8° (H) x 16.2° (V): D302 E model	AMBIENT LIGHT IMMUNITY	0 to 100,000 lux (D302)
PRINTING CONTRAST VALUE (min.)	PCS=23% (D302); PCS=45% (D302 E)	OPERATING TEMPERATURE	0 to 40 °C
READING ANGLE		STORAGE TEMPERATURE	-20 to 70 °C
Skew	±40° (D302); ±60° (D302 E)	HUMIDITY	0 to 95% non condensing
Pitch	±35° (D302); ±50° (D302 E)	DROP RESISTANCE	IEC 68-2-32 Test ED
Tilt	360° (D302/D302 E)		
SENSOR	640 X 480 element, 2D CCD array		
LASER CLASSIFICATION	Class 2 (IEC 825-1 and CDRH)		
BAR CODES			
1D Codes	2/5 Interleaved, Code 39, Code 128, Code 93, UPC/EAN/JAN, Codabar, RSS, CODE 39 Full ASCII, EAN 128, Composite Codes		



## READING CHARACTERISTICS

Lynx™ D302	1D CODE	DEPTH OF FIELD	Lynx™ D302 E	1D CODE	DEPTH OF FIELD
	Code 39 5 mils	75 to 105 mm		Code 39 5 mils	35 to 70 mm
	Code 39 20 mils	75 to 325 mm			
	EAN13 13 mils	45 to 115 mm			
Lynx™ D302	2D CODE	DEPTH OF FIELD	Lynx™ D302 E	2D CODE	DEPTH OF FIELD
	Postnet 20 mils	75 to 325 mm		PDF417 5 mils	40 to 75 mm
	PDF417 6.6 mils	45 to 160 mm		PDF417 10 mils	45 to 100 mm
	PDF417 10 mils	35 to 215 mm		QR 5 mils	45 to 60 mm
	QR 10 mils	55 to 105 mm		QR 10 mils	35 to 85 mm
	QR 15 mils	45 to 175 mm		Datamatrix 5 mils	45 to 60 mm
	Datamatrix 10 mils	60 to 120 mm		Datamatrix 10 mils	35 to 85 mm
	Datamatrix 15 mils	45 to 165 mm			



Product and company names and logos referenced may be either trademarks or registered trademarks of their respective companies.

We reserve the right to make modifications and improvements



**Datalogic S.p.A.**  
Italy  
Corporate Headquarters  
Tel. +39 051/3147011  
Fax +39 051/3147170  
info@datalogic.com

**Sales Italy**  
Tel. +39 051/3147011  
Fax +39 051/3147170  
sales@it.datalogic.com

**Sales International**  
(Central and South America, Far East, Middle East / Africa)  
Tel. +39 041/5986511  
Fax +39 041/5986550  
sales-intl@datalogic.com

**Australia**  
Datalogic PTY Ltd.  
Tel. +61 3/95589299  
Fax +61 3/95589233  
info@au.datalogic.com

**Germany**  
Datalogic GmbH  
Tel. +49 7026/6080  
Fax +49 7026/5746  
info@de.datalogic.com

**Sweden**  
Datalogic AB  
Tel. +46 40/385000  
Fax +46 40/385001  
info@se.datalogic.com

**Austria**  
Datalogic Handelsges mbH  
Tel. +43 2236/258820  
Fax +43 2236/258825  
info@at.datalogic.com

**Japan**  
Izumi Datalogic Co., Ltd.  
Tel. +81 78/3033400  
Fax +81 78/3033402  
idlmrke@izumi-datalogic.co.jp

**United Kingdom**  
Datalogic UK Ltd.  
Tel. +44 1582/464900  
Fax +44 1582/464999  
info@uk.datalogic.com

**Denmark**  
Datalogic AB  
Tel. +45 70/239970  
Fax +45 70/239972  
info@dk.datalogic.com

**Netherlands**  
Datalogic Optic Electronics BV  
Tel. +31 346/572888  
Fax +31 346/568736  
info@nl.datalogic.com

**USA**  
Datalogic Inc.  
Tel. +1 859/6897000  
Fax +1 859/3344970  
info@us.datalogic.com

**France**  
Datalogic France SA  
Tel. +33 1/60921111  
Fax +33 1/60921340  
info@fr.datalogic.com

**Spain**  
Datalogic Iberia  
Tel. +34 91/3837755  
Fax +33 91/3837962  
info@es.datalogic.com

**Datalogic Quality Partner**

